

SLFP2US-X

Face Plate Shuttered double Gang US

General Standards

- International standard: ISO/IEC 11801 2nd edition (2002) and ISO/IEC 11801 Amendment 2 (2010)
- European standard: EN 50173-1 (2002) and EN 50173-1 Amendment 1 (2009)
- U.S. Standard: ANSI/TIA/EIA 568-B.2-10 (2008)

Description

Silver link Faceplates 2-Port w/ID Windows Single

Physical Dimensions

- 1- **Materials:** Plastic - UL94V-0
- 2- **Weight:** 0.060 lbs.
- 3- **Dimensions:**
Height: 4.500 in.
Width: 2.750 in.
Depth: 0.260 in.
- 4- **Included Parts:** 6-32 screw, 2 carton label, clear window
- 5- **Termination area:** Indoor
- 6- **Packaging:** Individually packaged in a plastic bag.
- 7- **Color:** White / Off White



Electrical characteristics (Connectivity)

| | Specifications |
|--------------------------------|----------------|
| Connector/Hardware Retention | 20 lbs. |
| Storage Temperature Range | -40°C To +70°C |
| Installation Temperature Range | -10°C To +60°C |
| Operation Temperature Range | -10°C To +60°C |

Applicable Specifications and Agency Compliance (Overall)

| Applicable Standards & Environmental Programs | Specifications |
|---|-----------------------------|
| EU Directive 2002/95/EC (RoHS) | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy) | 01/10/2006 |
| MII Order #39 (China RoHS) | Yes |
| Safety Listing | Bi-national Standard Listed |
| Suitability | Specifications |
| Suitability - Indoor | Yes |

Product Family

| Item Number | White | Off White |
|------------------------------|-----------|------------|
| 1-Port Shuttered Single-gang | SLFP1US-W | SLFP1US-OW |
| 2-Port Shuttered Single-gang | SLFP2US-W | SLFP2US-OW |
| 4-Port Shuttered Single-gang | SLFP4US-W | SLFP4US-OW |

