

GLUC8o-6HT-A

Cat6 180 Degree Keystone Jack Module Tool Less Short Body

SPECIFICATION

- Meets ANSI/TIA-568-C.2 Category 6 Connecting Hardware

Electrical

- Insulation Resistance: 500 MΩm minimum @ 100 Vdc
- Dielectric Withstanding Voltage: 1000 Vac rms @ 60Hz for one minute
- Current Rating: 1.5 Amps
- Spring wire contact resistance: 20 MΩm maximum
- IDC Contact resistance: 2.5 MΩm maximum

Mechanical

- Total Contact force : >100 GRAMS per contact wire lead
- Retention : 50 N(11 lbf) for 60s ± 5s
- Durability : 750 cycles minimum
- Conductor compatibility : 22~24AWG
- Temperature range storage : -40° C ~ +70 C
- Temperature range operation : -10° C ~ +60 C
- Relative humidity operation : Maximum noncondensing 93%

Materials

- Housing: High Impact flame retardant plastic, UL 94 V-0 Rated
- PCB : FR4, 1.6mm thickness
- Spring wire : Phosphor Bronze Alloy plated with 50 micro-inch of gold over 70 ~ 100 micro-inch of nickel
- IDC : Phosphor Bronze alloy plated with 100 micro-inch of tin

